

TM 8 Centrifuge Extractor, 1500gm Capacity

- Centrifuge bowl rotation speed of 3000rpm
- Built with braking system for rapid stop
- Variable acceleration rate control from 0 to 3000rpm
- Aluminium rotor bowl equipped with a removable circular cover
- Supplied with pack of filter paper (50pcs)
- Safety lock container
- Power 240V 50Hz 1ph

STANDARD

ASTM D2172, AASHTO T15, T164

Also Available:

TM 8/A Centrifuge Extractor, 3000gm Capacity

- Rotation speed 2600rpm
- Supplied with a pack of filter paper (50pcs)
- Power 240V 50Hz 1ph

TM 9 Filter Paper - Pack of 50

Water Bath

Unit Test Digital Readout Thermostatic Control Stainless Steel Water Bath fitted with stirrer for water circulation, cover, internal stainless steel constructed and outernal fitted with anti-heat protection fibre.

General Specification

Model	UW 1	UW 2	UW 3/F
Capacity (litres)	23	30	48
Internal dimension (mm)	350 x 300 x 220(H)	450 x 300 x 220(H)	600 x 300 x 220(H)
Controller	Digital		
Temperature range (°C)	0-100 °c x 0.1 °c		
Power	240v 50Hz 1ph		
App Weight (kg)	9	15	18

TM 7 Automated Marshall Compactor

- Automated lifting and dropping device with standard dropping height
- Mounted on concrete base assembly with hardwood block and top plate
- Automatic digital counter for the control of number of compaction to the specimen, portable
- Built-in safety device to ensure automatic cut-off to prevent cover from opening

SPECIFICATION

- Hammer weight: 4.535kg
- Hammer drop: 457mm
- Hammer diameter: 99mm
- Approx. weight 230kg
- Power: 240V, 50Hz, 1ph
- Approx. dimension: 600 x 610 x 1900mm

STANDARD

BS 598, ASTM D1559, AASHTO T245

■ TM 8



■ UW 1



■ TM 7

